Evidence of Performance

Airborne sound insulation of building components

Test Report No. 13-001137-PR03 (PB 1-H01-04-en-02)



Client PRESS GLASS SA

Nowa Wies

Kopalniana 9 42-262 Poczesna Poland

	Product	Insu	lating	glass	unit
--	---------	------	--------	-------	------

Designation FL 6/12/FL 4/12/ VSG (FL 4/0.76 PVB SC/FL 4) kl.2/B/2 Ar

Overall dimensions (w x h)

) 1,230 mm × 1,480 mm

Construction 6/12/4/12/ 44.2 LSG SC

Gas filling Argon

Area related mass 45.4 kg/m²

Specials -/-

Weighted sound reduction index R_w Spectrum adaptation terms C and C_{tr}



 $R_w(C; C_{tr}) = 42 (-1;-6) \text{ dB}$

Building Acoustics

ift Rosenheim 02.10.2013

Dr. Joachim Hessinger, Dipl.-Phys. Head of Testing Department Building Physics Markus Schramm, M.Eng., Dipl.-Ing. (FH) Operating Testing Officer




EN ISO 10140-1: 2010

+A1:2012

EN ISO 10140-2 : 2010 EN ISO 717-1 : 1996+A1:2006

13-001137-PR03 (PB 1-H01-04-de-01) dated 01.10.2013

Representation



Instructions for use

This test report serves to demonstrate the airborne sound insulation of a building component.

Applicable for Germany

 R_w corresponds to $R_{w,P}$ for DIN 4109 annex 1 table 40

Validity

The data and results given relate solely to the tested and described specimen.

Testing the sound insulation does not allow any statement to be made on any further characteristics of the present construction regarding performance and quality.

Notes on publication

The **ift** Guidance Sheet "Conditions and Guidance for the Use of **ift** Test Documents" applies.

The cover sheet can be used as abstract.

Contents

The test report contains a total of 7 pages:

- 1 Object
- 2 Procedure
- 3 Detailed results
- 4 Instructions for use Data sheet (1 page)

